



SOCKET DETAIL

#	QTY.	MATERIAL	DESCRIPTION
1	1	ALUMINUM 6351-T6	BOLT-ON SOCKET ALUMINUM EXT.
2	1	ALUMINUM 6061-T6	1 1/4" SCH. 80 IPS PIPE (1.66" O.D) 1420mm LG.
3	1	ALUMINUM 6061-T6	30 O.D & 24mm I.D
4	2	ORANGE POLYETHYLENE	30mm END CAP
5	2	ALUMINUM 6061-T6	CLAMPS C/W S.S. 3/8"x1 1/4" BOLT, NUT AND WASHER
6	1	GREY POLYETHYLENE	TOP CAP
7	1	STAINLESS STEEL 316	5/16" X 3/4" SOCKET HEAD SCREW C/W NYLON INSERT LOCK NUT

THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION AND OTHER RIGHTS WHICH ARE THE SOLE AND EXCLUSIVE PROPERTY OF MSU MISSISSAUGA LTD.

POSSESSION OF THIS MATERIAL DOES NOT CONVEY OR TRANSFER ANY RIGHTS THEREIN, AND REPRODUCTION, USE, COPYING OR DISCLOSURE TO OTHERS IS FORBIDDEN WITHOUT THE PRIOR WRITTEN CONSENT OF AN OFFICER OF MSU MISSISSAUGA LTD.

© MSU MISSISSAUGA LTD. - JULY 23RD, 2014

NOTE: 1) WELDING SHALL CONFORM TO CSA W47.2 & CSA W59.2

2) GROUND ROUGH EDGES SMOOTH. WELDED SURFACES REMAIN AS WELDED.

3) RUNG CROSS SECTION MUST BE SPECIFIED, 20mmØ RUNG SHOWN.

PROJECT	LOCATION
CONTRACTOR	PROJECT
ARCHT/ENGR	CONTRACTOR
QTY.	ENGINEER
#	#

TITLE					
MODEL #3100 PERMANENT 'T' SAFETY HANDLE BOLT-ON STYLE					
NO.	DATE	BY	DATE	DWG. BY:	PLN. NO.
1			##/##/##	SCJ	CATA
SCALE	NTS		CHK'D BY:	DWG. NO.	
				3100-3	