



#	QTY.	MATERIAL	DESCRIPTION
1	2	ALUMINUM 6061-T6	FRAME EXTRUSION # S8984
1A	2	ALUMINUM 6061-T6	FRAME EXTRUSION # S8983
2	2	ALUMINUM 6061-T6	6.4mm TREAD PLATE
3	14	ALUMINUM 6061-T6	76X6mm FLAT BAR REINFORCING
4	18	ALUMINUM 6061-T6	38 X 64 X 6MM CASTIN ANCHOR
5	2	STAINLESS STEEL 316	90 DEG. HOLD OPEN ARM
6	2	STAINLESS STEEL 316	3" CONT. HINGE C/W 1/4" TAMPERPROOF FASTENERS & 6X42mm ALUM. FLAT BAR
7	2	ALUMINUM 6061-T6	RECESSED DROP HANDLE
8	4	ALUMINUM 6061-T6	LOCK TAB WELDED TO ITEM #1A

THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION AND OTHER RIGHTS WHICH ARE THE SOLE AND EXCLUSIVE PROPERTY OF MSU MISSISSAUGA LTD.

POSSESSION OF THIS MATERIAL DOES NOT CONVEY OR TRANSFER ANY RIGHTS THEREIN, AND REPRODUCTION, USE, COPYING OR DISCLOSURE TO OTHERS IS FORBIDDEN WITHOUT THE PRIOR WRITTEN CONSENT OF AN OFFICER OF MSU MISSISSAUGA LTD.

© MSU MISSISSAUGA LTD. - JULY 23RD, 2014

- NOTE: 1) ALL ALUMINUM SURFACES IN CONTACT WITH CONCRETE SHALL RECEIVE 2 COATS OF BITUMINOUS PAINT.
 2) WELDING SHALL CONFORM TO CSA W47.2 & CSA W59.2
 3) GROUND ROUGH EDGES SMOOTH. WELDED SURFACES REMAIN AS WELDED.
 4) REINFORCED TO WITHSTAND A LIVE LOAD OF 300 LBS/SQ.FT (14.4KPa)

PROJECT	LOCATION PROJECT	
CONTRACTOR	CONTRACTOR	
ARCHT/ENG'R	ENGINEER	
QTY.	1	PROJECT NO. #

TITLE MSU TYPE-CD ALUM. ACCESS HATCH 1200 X 1200MM CLEAR OPENING					
NO.	DATE	BY	DATE	DWG. BY	PL. NO.
1			##/##/##	SCJ	CATA
SCALE	NTS		DWG. NO.	C-2	