



#	QTY.	MATERIAL	DESCRIPTION
1	6	ALUMINUM 6061 T-6	38 X 38 X 6mm ANGLE 38MM LG
2	6	STAINLESS STEEL 304	3/8 X 3 3/4' WEDGE ANCHOR C/W NUT AND FLAT WASHER
3	4	ALUMINUM 6061 T-6	3MM PLATE
4	2	STYROFOAM SM BLUE	3" THICK INSULATION
5	8	STAINLESS STEEL 304	1/4' X 3 1/2' HEX BOLT C/W WASHERS
6	2	STAINLESS STEEL 304	6mmØ U-BOLT HANDLE

THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION AND OTHER RIGHTS WHICH ARE THE SOLE AND EXCLUSIVE PROPERTY OF MSU MISSISSAUGA LTD.

POSSESSION OF THIS MATERIAL DOES NOT CONVEY OR TRANSFER ANY RIGHTS THEREIN, AND REPRODUCTION, USE, COPYING OR DISCLOSURE TO OTHERS IS FORBIDDEN WITHOUT THE PRIOR WRITTEN CONSENT OF AN OFFICER OF MSU MISSISSAUGA LTD.

© MSU MISSISSAUGA LTD. - JULY 23RD, 2014

NOTE: 1) ALL ALUMINUM SURFACES IN CONTACT WITH CONCRETE SHALL RECEIVE 2 COATS OF BITUMINOUS PAINT.
 2) WELDING SHALL CONFORM TO CSA W47.2 & CSA W59.2
 3) GROUND ROUGH EDGES SMOOTH. WELDED SURFACES REMAIN AS WELDED.

PROJECT	LOCATION PROJECT	
CONTRACTOR	CONTRACTOR	
ARCHT/ENGR	ENGINEER	
QTY.	1	PROJECT NO. #

TITLE					
MSU CIRCULAR FROST COVER					
NO.	DATE	BY	DATE	DATE	PL. NO.
1			###/##/##	SCJ	CATA
REVISION			SCALE	DWG. NO.	
			NTS		FROSTP-1